

# ULTIMATE RB™

A **CARLISLE** COMPANY



## ULTIMATE-TOUGH™ Rolls & Tiles



Popular in health and fitness clubs, weight rooms, and sports arenas, **ULTIMATE-TOUGH** recycled rubber flooring is a champion in a wide variety of applications.

### Features

- High Impact Durability
- Slip Resistant
- Sound Absorption Properties
- Comfort Underfoot
- Low Maintenance
- Environmentally Friendly
- Standard Roll & Tile Format
- Custom Size & Color Options

### Applications:

- Health & Fitness Clubs
- School Weight & Locker Rooms
- Education Multipurpose Rooms
- Athletic Facilities
- Sports Venues
- Production & Distribution Floors

ULTIMATE-TOUGH recycled rubber flooring is ideal for your high-wear and high-impact spaces that require maximum subfloor protection. Commercial, Industrial, Main Street, and Residential spaces can benefit from durable rubber flooring. Manufactured with up to 93% post-consumer recycled rubber content for all black, and up to 88% with small percentages of colored EPDM, ULTIMATE-TOUGH stands up to high-activity and foot traffic while providing high-impact durability, comfort underfoot and slip resistance in wet or dry conditions. This environmentally friendly flooring is low maintenance and made in the USA.



**ULTIMATERB.com**

904 NE 10<sup>th</sup> Avenue  
McMinnville, OR 97128  
(800) 525-5530

Main manufacturing/shipping locations include Oregon and Ohio.



CERTIFIED BY  
SCS Global Services





# ULTIMATE-TOUGH™

## Rolls & Tiles



### Standard Tile Sizes

#### Standard Tile Sizes

	9.5mm thickness & 20% color
Zip-Tile	28.5" x 28.5" (0.72m x 0.72m) 5.64 sq. ft.
	8mm thickness & 10% color
Tru-Lock Tile	24" x 24" (0.61m x 0.61m) 4 sq. ft.

Custom sizes and colors available



### Roll Dimensions

#### Standard Roll Sizes

	6.4mm (0.252") & 10% color 8mm (0.315") & 10% color 9.5mm (0.374") & 20% color 12mm (0.472") & 20% color Tolerance +/- 0.020"
Thickness	
	4 ft. (1.22m) Tolerance - 0.00", +0.75"
Width	
	25 ft. (7.62m) 50 ft. (15.24m) Tolerance - 0.00", +3.0"
Length	

Custom sizes and colors available

### Color Options

Please visit [ULTIMATERB.com](http://ULTIMATERB.com) for current available color options.



### Specifications

Test Type	Test	Result
Density	ASTM D297	64-80 lbs/ft <sup>3</sup>
Hardness	ASTM D2240	65 +/- 5
Tear Strength	ASTM D624	64 PLI
Elongation (at break)	ASTM D412	105%
Tensile Strength	ASTM D412	285 PSI
Compression Set	ASTM D395	18.5% @ 25%
Static Load Limit	ASTM F970	0.005" (@400 PSI)
Coefficient of Friction	ASTM D2047	0.97 dry Neolite 0.91 wet Neolite
Coefficient of Friction	ASTM D1894	1.45
Abrasion Resistance	ASTM D3389	<1g, 1,000 cycle
Resistance to Chemicals	ASTM F925	No Change/Slight-Dulling
Floor Ignition	ASTM D2859	Meets
Critical Radiant Flux	ASTM E648	Class II*
IIC (6" slab no ceiling)	ASTM E492	52
STC (6" slab no ceiling)	ASTM E90	52
Delta IIC	ASTM E2179	22

Note: Physical properties can vary by product type. Data Sheet information applies to this product only.

\*Class II in buildings equipped throughout with an automatic sprinkler system.

### Maintenance & Floor Care

Maintenance and floor care depend on the desired appearance of the installed product and the type of equipment used to maintain the flooring. Use only Ultimate RB recommended cleaners, disinfectant, and neutral PH, non-petroleum products. Do not use harsh chemicals.

### Warranty

5-year limited warranty for manufacturer defects when installed according to manufacturer instructions.